



PRE-RELEASE INFORMATION

VHF AND UHF IDAS™ DIGITAL TRANSCEIVERS

IC-F3202DEX

(IDAS digital VHF transceiver)

Approval pending

IC-F4202DEX

(IDAS digital UHF transceiver)

Approval pending

IECEEx/ATEX INTRINSICALLY SAFE RADIO



IEC Certifications

Mining : Ex ib I Mb
Gas : Ex ib IIC T4 Gb
Dust : Ex ib IIIC IP6x T110°C Db
-20°C≤Ta≤+55°C

ATEX Certifications

Mining : I M2 Ex ib I Mb
Gas : II 2G Ex ib IIC T4 Gb
Dust : II 2D Ex ib IIIC IP6x T110°C Db
-20°C≤Ta≤+55°C

Certification pending at time of printing. Subject to change.

IP67 Dust-tight & Waterproof Protection

The IC-F3202DEX series provides rugged protection against dust and water that is equivalent to IP67. The IC-F3202DEX series can withstand 1m depth of water for 30 minutes and its dust-tight construction shuts out powder dust, sand and other objects.

dPMR™ Mode 1/2 Operation

The IC-F3202DEX series provides basic operation in dPMR Mode 1, 2 conventional mode. It is also compatible with Mode 2 multi-site system. The following dPMR features are programmable.

- PTT ID (TX)
- Individual/Group call
- CC (Channel Code)
- Power ON/OFF status call (TX)
- Stun/kill/revive (RX)
- Ambience listening (RX)
- Enhanced emergency
- Lone worker/Man down function
- Digital voice scrambler

TX: Transmit, RX: Receive

Man Down and Lone Worker Functions for Emergency Call

The man down function automatically sends an emergency signal when the transceiver is left in a horizontal position for a preset period. The lone worker function also can transmit an emergency signal when the radio is not operated for a preset period. These emergency functions can be used to alert your co-workers or dispatcher to any potential trouble.

Other Features

- 16 memory channels with channel announcement function
- Built-in 2-Tone, 5-Tone, CTCSS and DTCS
- BIIS 1200 PTT ID transmission
- Voting scan
- DTMF autodial
- Three programmable buttons (including emergency red button)
- Low electrical resistivity body; Carrying case is not required
- 19.5–21 hours* operating time with BP-277EX

* Tx: Rx: Standby=5:5:90. Power save on.

- Optional waterproof speaker-microphone, HM-203EX

SPECIFICATIONS

	IC-F3202DEX	IC-F4202DEX
GENERAL		
Frequency coverage	136–174MHz	400–470MHz
Number of channels	16 channels	
Type of emission	16K0F3E, 14K0F3E, 8K50F3E, 4K00F1E/F1D	
Channel spacing	25/20/12.5/6.25kHz	
Power supply requirement	7.4V DC nominal	
Current drain (approx.)		
Tx High	550mA	550mA
Rx Max. audio	300mA (Internal SP)	300mA (Internal SP)
Standby	110mA (Digital mode)	110mA (Digital mode)
Antenna impedance	50Ω	
Operating temperature range	–25°C to +55°C (Radio only)	
Dimensions (W×H×D)	63×144×50mm (With BP-277EX)	
(Projections not included)		
Weight (approx.)	258g (Radio only)	
	466g (With MB-94EX, BP-277EX & FA-SC55V)	
TRANSMITTER		
Output power (at 7.4V DC)	1W, 0.8W, 0.6W (Hi, L2, L1)	
Max. frequency deviation	±5.0kHz/±4.0kHz/±2.5kHz/±6.25kHz (W/M/N/D)	
Frequency stability	±1.0ppm	
Spurious emissions	0.25μW (≤ 1GHz), 1.0μW (> 1GHz)	
Residual modulations	54/53/50dB typ. (W/M/N)	48/46/42dB typ. (W/M/N)
Audio harmonic distortion	1.0/1.0/1.5% typ. (AF 1kHz 40% deviation, W/M/N)	
FSK error	5.0% max.	
Ext. microphone connector	14-pin multi-connector/2.2kΩ	
RECEIVER		
Sensitivity Analogue	–4dBμV typ. emf (at 20dB SINAD)	
Digital	–8dBμV typ. emf (at 5% BER)	
Adjacent channel selectivity	78/75/70/62dB typ. (W/M/N/D)	74/72/68/57dB typ. (W/M/N/D)
Spurious response rejection	85dB typ.	90dB typ.
Intermodulation rejection	67dB typ. (W/M/N)	
	73dBμV typ. emf (Digital)	
Hum and noise (With CCITT filter)	53/51/48dB typ. (W/M/N)	53/51/47dB typ. (W/M/N)
Audio output power		
Internal SP (With 32Ω load)	400mW typ. (at 5% distortion)	
External SP (With 32Ω load)	400mW typ. (at 5% distortion)	
Ext. speaker connector	14-pin multi-connector/32Ω	

Measurements made in accordance with EN 300-086, EN 301-166.

All stated specifications are subject to change without notice or obligation.

Applicable U.S. Military Specifications & IP Rating

Standard	MIL 810G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I-C
Solar Radiation	505.5	I
Rain Blowing/Drip	506.5	I, III
Humidity	507.5	II
Salt Fog	509.5	–
Dust Blowing	510.5	I
Immersion	512.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Ingress Protection Standard

Dust & Water	IP67 (Dust-tight and waterproof)
--------------	----------------------------------

MIL Specifications and IP rating test are under evaluation as of November 2013.

Supplied accessories: (May differ according to version)

- Battery pack, BP-277EX
- Belt clip, MB-94EX
- Antenna
- Battery charger, BC-212EX
- AC adapter, BC-123S

This device has not been approved by the appropriate authorities in each country. This device may not be sold or leased, or be offered for sale or lease, until approval has been obtained. All stated features, appearances, and specifications may be subject to change without notice.

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in the United States, the United Kingdom, Germany, France, Spain, Russia and/or other countries. IDAS and IDAS logo are trademarks of Icom Incorporated. dPMR and the dPMR logo are trademarks of the dPMR MoU Association. All other trademarks are the properties of their respective holders.

Icom Inc.

1-1-32, Kami-minami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

www.icom.co.jp/world

Count on us!

Icom America Inc.

12421 Willows Road
Kirkland, WA 98034, U.S.A.
Phone: +1 (425) 454-8155
Fax: +1 (425) 454-1509
E-mail: sales@icomamerica.com
URL: <http://www.icomamerica.com>

Icom Canada

Glenwood Centre #150-6165 Highway 17,
Delta, B.C., V4K 5B8, Canada
Phone: +1 (604) 952-4266
Fax: +1 (604) 952-0090
E-mail: info@icomcanada.com
URL: <http://www.icomcanada.com>

Icom Brazil

Rua Itororó, 444 Padre Eustáquio
Belo Horizonte MG,
CEP: 30130-150, Brazil
Phone: +55 (31) 3582 8847
Fax: +55 (31) 3582 8987
E-mail: sales@icombrasil.com

Icom (Europe) GmbH

Communication Equipment
Auf der Krautweide 24
65812 Bad Soden am Taunus, Germany
Phone: +49 (6196) 76885-0
Fax: +49 (6196) 76885-50
E-mail: info@icom-europe.com
URL: <http://www.icomeurope.com>

Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer"
Bajos A 08174, Sant Cugat del Valles,
Barcelona, Spain
Phone: +34 (93) 590 26 70
Fax: +34 (93) 589 04 46
E-mail: icom@icomspain.com
URL: <http://www.icomspain.com>

Icom Polska Sp. z o.o.

80-286 Gdansk, Jaskowa Dolina St. 75, Poland
Phone: +48 (58) 551 0484
Fax: +48 (58) 551 4720
E-mail: icompolska@icompolska.com.pl
URL: <http://www.icompolska.com.pl>

Icom (UK) Ltd.

Blacksole House, Altrira Park,
Herne Bay, Kent, CT6 6GZ, U.K.
Phone: +44 (0) 1227 741741
Fax: +44 (0) 1227 741742
E-mail: info@icomuk.co.uk
URL: <http://www.icomuk.co.uk>

Icom France s.a.s.

Zac de la Plaine,
1 Rue Brindejonc des Moulinais, BP 45804,
31505 Toulouse Cedex 5, France
Phone: +33 (5) 61 36 03 03
Fax: +33 (5) 61 36 03 00
E-mail: icom@icom-france.com
URL: <http://www.icom-france.com>

Icom (Australia) Pty. Ltd.

Unit 1 / 103 Garden Road,
Clayton, VIC 3168 Australia
Phone: +61 (03) 9549 7500
Fax: +61 (03) 9549 7505
E-mail: sales@icom.net.au
URL: <http://www.icom.net.au>

Icom New Zealand

146A Harris Road, East Tamaki,
Auckland, New Zealand
Phone: +64 (09) 274 4062
Fax: +64 (09) 274 4708
E-mail: inquiries@icom.co.nz
URL: <http://www.icom.co.nz>

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone: +886 (02) 2559 1899
Fax: +886 (02) 2559 1874
E-mail: sales@asia-icom.com
URL: <http://www.asia-icom.com>

Shanghai Icom Ltd.

No.101, Building 9, Caifuxingyuan Park,
No.188 Maoting Road, Chedun Town,
Songjiang District, Shanghai, 201611, China
Phone: +86 (021) 6153 2768
Fax: +86 (021) 5765 9987
E-mail: bjicom@bjicom.com
URL: <http://www.bjicom.com>

OPTIONS

BATTERY PACK

BP-277EX
Li-Ion, 7.4V
1800mAh (min.)
1900mAh (typ.)



RAPID CHARGER

BC-123S¹ **BC-212EX**



Charges the BP-277EX in 2 hours (approx.).

SPEAKER-MICROPHONE

HM-203EX



BELT CLIP

MB-94EX
Alligator type
Same as supplied.



ANTENNAS

- FA-SC25V : 136–150MHz
- FA-SC55V : 150–174MHz
- FA-SC25U : 400–430MHz
- FA-SC57U : 430–470MHz

¹ BC-123SA for 120V AC.
SE for 230V AC. SV for 240V AC.

DO NOT use the transceiver with any other equipment other than the above options.

ATEX mining protection and meaning

I	M2	Ex	ib	I	Mb	Mb = Mining equipment protection level: High protection
						I = Protection in mining group: Methane
						ib = Intrinsic safety
						Ex = Explosion proof equipment
						M2 = Must be switched OFF in case of firedamp
						I = Group I, Mining

ATEX gas protection and meaning

II	2	G	Ex	ib	IIC	T4	Gb	Gb = GAS equipment protection level: High protection
								T4 = Device surface temperature will not exceed 135°C
								IIC = Protection in GAS group: Acetylene, Hydrogen
								ib = Intrinsic safety
								Ex = Explosion proof equipment
								G = Gas, vapour and mist
								2 = High level protection for use in Zone 1 (gas)
								II = Group II, other (non-mining) areas

ATEX dust protection and meaning

II	2	D	Ex	ib	IIC	IP6x	T110°C	Db	Db = Dust equipment protection level: High protection
									T110°C = Maximum temperature of device surface
									IP6x = dust penetration protection
									IIC = Dust group: Conductive dust (R≤10 ³ Ωm)
									ib = Intrinsic safety
									Ex = Explosion proof equipment
									D = Dust
									2 = High level protection for use in Zone 21 (dust)
									II = Group II, other (non-mining) areas

Certification pending at time of printing. Subject to change. The International Electrotechnical Commission's safety standard certification is also pending.

* Please ensure the IC-F3202DEX/F4202DEX rating is acceptable for the intended place of use.

Your local distributor/dealer: